



## SL220A

3W LED spike light

### FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tilttable (°)	90
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>70
Colour Consistency	SDCM3
Rotation angle (°)	Fixed

### INSTALLATION INFORMATION

Input	350mA DC
Maximum Ambient Temperature	35°C
Weight	700g
Inrush Current	N/A
Construction Material	Anodised aluminium
UK Bathroom Zone	1
Electric Class (1, 2, 3)	III
Earth Leakage	N/A
Suitable for coastal areas	Yes

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m
SL220A F NW	Silver anodised aluminium	3W	4000K	38°	310	103	705

### WIRING INFORMATION

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PSIP70018W	220-240V	Yes	No	1	1	8

### ACCESSORIES

JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
GS220	Stylish, baffle-style snoot, perfect for creating a moonlighting effect	Sold Separately



COLLINGWOOD  
LIGHTING

LIGHTING INNOVATION

3W

Equivalent to 20W halogen

Long spike included for extra stability

Robust cable for outdoor use

### WARRANTY

Warranty

1 year

### FEATURES & BENEFITS

Available in anodised aluminium

PATENT: **GB2487912 GB2512715**