



# SL220 MAINS VOLTAGE

Mains Voltage LED Spike light

# **FEATURES**

IP rating	IP65
CSP Switchable	Single CCT
Tiltable (°)	90
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	Fixed

## INSTALLATION INFORMATION

Input	220-240V AC			
Maximum Ambient Temperature	55°C			
	SL220AB: TBC, SL220BK:			
Weight	714g, SL220SS: 1156g,			
	SL220BZ: 694g			
Inrush Current	0.07ms 5.2A			
Construction Material	Anodised aluminium			
UK Bathroom Zone	N/A			
SELV	Yes			
Electric Class (1, 2, 3)				
Earth Leakage	0.1			
Suitable for coastal areas	Yes			

### PHOTOMETRICS @ 25°C

Product code	Finish	Туре	w	Colour	Beam	lm	lm/W	Energy
SL220BK22MS	Black	Mains	5.7W	2200K	12°	431	76	A E

Energy rating is a reflection of the LED light source.

#### WIRING INFORMATION

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Parallel

#### **ACCESSORIES**

JB5	Gel filled waterproof connector	Sold Separately
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
GS220	Stylish, baffle-style snoot, perfect for creating a moonlighting effect	Sold Separately



LIGHTING INNOVATION



5.7W



Coastal protected



IP65 ideal for outdoor areas

## WARRANTY

Warrant

7 vears

### FEATURES & BENEFITS

Tiltable for flexible lighting direction to help suit any installation

SDCM3 ensuring uniform light appearance and consistency

Single LED and lens combination for maximum efficiency and optimal light distribution

Choice of material finish to suit different styles



