



**5.7W** 5.7W

 Coastal protected

**IP65** IP65 ideal for outdoor areas

## SL220 MAINS VOLTAGE

Mains Voltage LED Spike light

### FEATURES

<b>IP rating</b>	IP65
<b>CSP Switchable</b>	Single CCT
<b>Tilttable (°)</b>	90
<b>Dimmable Option</b>	No
<b>LED Lifetime</b>	L70 70,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM3
<b>Rotation angle (°)</b>	Fixed

### INSTALLATION INFORMATION

<b>Input</b>	220-240V AC
<b>Maximum Ambient Temperature</b>	55°C
	SL220AB: TBC, SL220BK:
<b>Weight</b>	714g, SL220SS: 1156g, SL220BZ: 694g
<b>Inrush Current</b>	0.07ms 5.2A
<b>Construction Material</b>	Stainless Steel 316
<b>UK Bathroom Zone</b>	N/A
<b>SELV</b>	Yes
<b>Electric Class (1, 2, 3)</b>	I
<b>Earth Leakage</b>	0.1
<b>Suitable for coastal areas</b>	Yes

### PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Energy
SL220SS30MS	Stainless steel	Mains	5.7W	3000K	12°	520	91	
SL220SS40MS	Stainless steel	Mains	5.7W	4000K	12°	538	94	
SL220SS22MF	Stainless steel	Mains	5.7W	2200K	40°	431	76	
SL220SS27MF	Stainless steel	Mains	5.7W	2700K	40°	515	90	
SL220SS30MF	Stainless steel	Mains	5.7W	3000K	40°	520	91	
SL220SS40MF	Stainless steel	Mains	5.7W	4000K	40°	538	94	
SL220AB22MS	Antique brass	Mains	5.7W	2200K	12°	431	76	
SL220AB27MS	Antique brass	Mains	5.7W	2700K	12°	515	90	
SL220AB30MS	Antique brass	Mains	5.7W	3000K	12°	520	91	
SL220AB40MS	Antique brass	Mains	5.7W	4000K	12°	538	94	

Energy rating is a reflection of the LED light source.

### WIRING INFORMATION

<b>Cable / Flying Lead</b>	3m H05RN-F rubberised cable (outside diameter: 6mm)
<b>Type of Wiring Required</b>	Parallel

### ACCESSORIES

<b>JB5</b>	Gel filled waterproof connector	Sold Separately
<b>GH220</b>	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
<b>GS220</b>	Stylish, baffle-style snoot, perfect for creating a moonlighting effect	Sold Separately

### WARRANTY

Warranty 7 years

### FEATURES & BENEFITS

Tilttable for flexible lighting direction to help suit any installation

SDCM3 ensuring uniform light appearance and consistency

Single LED and lens combination for maximum efficiency and optimal light distribution

Choice of material finish to suit different styles

BEAM ANGLE: **40°**

