



SL230 MAINS

Mains voltage LED twin pole spike light

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tilttable	90°
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	330°

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	SL230B: 1578g SL230D: 3500g SL230Z: 1577g
Inrush Current	120A 37ms
Construction Material	Anodised aluminium
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
SL230ZWBM30	Bronze anodised aluminium	11.4W	3000K	40°	1040	2x91	2x1182	
SL230BWB27	Black anodised aluminium	11.4W	2700K	40°	1030	2x90	2x1171	
SL230BWB30	Black anodised aluminium	11.4W	3000K	40°	1040	2x91	2x1182	
SL230DWB27	Stainless steel	11.4W	2700K	40°	1030	2x90	2x1171	
SL230DWB30	Stainless steel	11.4W	3000K	40°	1040	2x91	2x1182	

WIRING INFORMATION

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	(H05RN-F) 3 CORE rubberised cable (OD: 7mm)

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	No	N/A

ACCESSORIES

JB5	Gel filled waterproof connector	Sold Separately
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
GS220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately

11.4W

11.4W



Coastal protected

IP65

IP65 ideal for outdoor areas

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Adjustable pole-mounted twin heads are perfect for illuminating paths, steps and trees

Easily ground mounted with spiked pole and single cable for quick installation

Elegant and discreet black and bronze finishes

Mains voltage for easy installation

Highly efficiency of 93lm/W

