

5.7W 5.7W



Coastal protected

IP65

IP65 ideal for outdoor areas

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

High efficacy of 91lm/W

Single LED and lens combination for maximum efficiency and optimal light distribution

Choice of material finish to suit different styles

Choose from a range of hoods for reduced glare.



GH220B



GS220B

SL230 SINGLE HEAD MAINS

Mains voltage single head LED spike light

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tilttable (°)	90
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	330

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	50°C
Weight	1.18
Inrush Current	60A 37ms (SLM230SH_...)
Construction Material	Anodised aluminium
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	I
Earth Leakage	0.1
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
SLM230SHB30	Black	5.7W	3000K	40°	520	91	1182	

WIRING INFORMATION

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	(H05RN-F) 3 CORE rubberised cable (OD: 7mm)

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	N/A	N/A

ACCESSORIES

JB5	Gel filled waterproof connector	Sold Separately
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
GS220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately

