



SL230

Low voltage LED twin pole spike light

Features

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	90°
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	330°

Installation Information

Input	350mA / 700mA
Maximum Ambient Temperature	35°C
Weight	SL230B: 1432g SL230D: 3200g SL230Z: 1401g
Inrush Current	N/A
Construction Material	Anodised aluminium
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	Colour	Beam	W	lm	lm/W	Ix @ 1m	W	lm	lm/W	Ix @ 1m	Energy
				350mA				700mA				
SL230ZWBX27	Bronze anodised aluminium	2700K	40°	4.4W	580	135	2 x 659	9.2W	1030	111	2 x 1171	
SL230ZWBX30	Bronze anodised aluminium	3000K	40°	4.4W	600	140	2 x 682	9.2W	1040	112	2 x 1182	
SL230BWBX27	Black anodised aluminium	2700K	40°	4.4W	580	135	2 x 659	9.2W	1030	111	2 x 1171	
SL230BWBX30	Black anodised aluminium	3000K	40°	4.4W	580	140	2 x 682	9.2W	1030	112	2 x 1182	
SL230DWBX30	Stainless steel	3000K	40°	4.4W	580	140	2 x 682	9.2W	1030	112	2 x 1182	

Wiring Information

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	(H05RN-F) 2 CORE rubberised cable (OD: 6mm)

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV150700	220-240V	Yes		N/A		
PSIP70036W	220-240V	Yes	No	1	2	3

Accessories

JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
GS220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately



4.4W at 350mA or 9.2W at 700mA



Coastal protected



IP65 ideal for outdoor areas

Guarantee

Warranty 7 years

Features & benefits

- Adjustable pole-mounted twin heads are perfect for illuminating paths, steps and trees
- Easily ground mounted with spiked pole and single cable for quick installation
- Elegant and discreet black and bronze finishes
- Highly efficiency of 114lm/W
- Discreet cabling
- Additional accessories also available such as hoods and snoots

