



4.4W at 350mA or 9.2W at 700mA



Coastal protected



IP65 ideal for outdoor areas

## WARRANTY

Warranty

7 years

## FEATURES & BENEFITS

Adjustable pole-mounted twin heads are perfect for illuminating paths, steps and trees

Easily ground mounted with spiked pole and single cable for quick installation

Elegant and discreet black and bronze finishes

Highly efficiency of 114lm/W

Discreet cabling

Additional accessories also available such as hoods and snoots

## SL230

Low voltage LED twin pole spike light

### FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tilttable (°)	90
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	330

### INSTALLATION INFORMATION

Input	350mA / 700mA DC
Maximum Ambient Temperature	35°C
Weight	SL230B: 1432g SL230D: 3200g SL230Z: 1401g
Inrush Current	N/A
Construction Material	Anodised aluminium
UK Bathroom Zone	N/A
SELV	N/A
Electric Class (1, 2, 3)	III
Earth Leakage	N/A
Suitable for coastal areas	Yes

### Photometrics @ 25°C

Product Code	Finish	Colour	Beam	W	lm	lm/W	lx @ 1m	W	lm	lm/W	lx @ 1m	Energy
				350mA				700mA				
SL230ZWBX27	Bronze anodised aluminium	2700K	40°	4.4W	580	135	2 x 659	9.2W	1030	111	2 x 1171	
SL230ZWBX30	Bronze anodised aluminium	3000K	40°	4.4W	600	140	2 x 682	9.2W	1040	112	2 x 1182	
SL230BWBX27	Black anodised aluminium	2700K	40°	4.4W	580	135	2 x 659	9.2W	1030	111	2 x 1171	
SL230BWBX30	Black anodised aluminium	3000K	40°	4.4W	580	140	2 x 682	9.2W	1030	112	2 x 1182	
SL230DWBX30	Stainless steel	3000K	40°	4.4W	580	140	2 x 682	9.2W	1030	112	2 x 1182	

### WIRING INFORMATION


Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	(H05RN-F) 2 CORE rubberised cable (OD: 6mm)

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV150700 (all settings)	220-240V	Yes	No	N/A		
DRV350700TD (700mA)	220-240V	Yes	Yes	N/A		
PSIP70036W	220-240V	Yes	No	1	2	3

### ACCESSORIES

JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
GS220	Simple hood to reduce glare whilst maintaining a good light	Sold Separately





## LIGHTING INNOVATION

Sleek and contemporary, these twin pole spike lights offer a great new and practical way to illuminate your landscape with interesting and discreet lighting angles. Featuring two SL220 spike light luminaires with one leader cable, you can direct light up or down via rotatable heads, for perfect illumination of pathways, features and trees. Features include IP65 rating for outdoor use, efficacy of 144lm/W, tiltable up to 90 degree and rotatable up to 330 degree. There are also straight to mains and low voltage options, three colour temperatures to choose from and a bronze finish version. A seven-year warranty is also available. Upgrade the look and feel of your spike light with a simple low glare hood or snoot, for optimum light distribution, or calming moonlight effect.