



collingwood



11.4W

Coastal protected

IP65 ideal for outdoor areas

SL240 Mains

Mains voltage LED twin bar spike light

Features

IP rating	IP65
CSP Switchable	Single CCT
Tilttable	90°
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	330°

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	SL240B: 1584g SL240D: 2700g SL240Z: 1414g
Inrush Current	120A 37ms
Construction Material	Anodised aluminium Stainless Steel 316
Suitable for coastal areas	Yes

Guarantee

Features & benefits

- Adjustable bar-mounted twin heads, ideal for discreet illumination of shrubbery, trees and other landscape features
- Easily ground mounted with two spikes and single cable for quick installation
- Elegant and discreet black and bronze finishes
- Mains voltage for easy installation
- Highly efficiency of 93lm/W

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
SL240ZWBM27	Bronze anodised aluminium	11.4W	2700K	40°	1030	2 x 90	2 x 1171	
SL240ZWBM30	Bronze anodised aluminium	11.4W	3000K	40°	1040	2 x 91	2 x 1182	
SL240BWB27	Black anodised aluminium	11.4W	2700K	40°	1030	2 x 90	2 x 1171	
SL240BWB30	Black anodised aluminium	11.4W	3000K	40°	1040	2 x 91	2 x 1182	
SL240DWB30	Stainless steel	11.4W	3000K	40°	1040	2 x 91	2 x 1182	

Wiring Information

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	(H05RN-F) 3 CORE rubberised cable (OD: 7mm)

LED Driver

Driver	Input
N/A (integrated SELV driver)	220-240V

Accessories

JB5	Gel filled waterproof connector	Sold Separately
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
GS220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately

