

11.4W

Coastal protected

IP65 ideal for outdoor areas

## FEATURES & BENEFITS

Adjustable bar-mounted twin heads, ideal for discreet illumination of shrubbery, trees and other landscape features

Easily ground mounted with two spikes and single cable for quick installation

Elegant and discreet black and bronze finishes

Mains voltage for easy installation

Highly efficiency of 93lm/W



## SL240 MAINS

Mains voltage LED twin bar spike light

### FEATURES

<b>IP rating</b>	IP65
<b>CSP Switchable</b>	Single CCT
<b>Tilttable (°)</b>	90
<b>LED Lifetime</b>	L70 70,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM3
<b>Rotation angle (°)</b>	330

### INSTALLATION INFORMATION

<b>Input</b>	220-240V AC
<b>Maximum Ambient Temperature</b>	35°C
<b>Weight</b>	SL240B: 1584g SL240D: 2700g SL240Z: 1414g
<b>Inrush Current</b>	120A 37ms
<b>Construction Material</b>	Anodised aluminium Stainless Steel 316
<b>Suitable for coastal areas</b>	Yes

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
SL240DWBM30	Stainless steel	11.4W	3000K	40°	1040	2x91	2x1182	

### WIRING INFORMATION

<b>Cable / Flying Lead</b>	3m H05RN-F rubberised cable (outside diameter: 7mm)
<b>Type of Wiring Required</b>	Parallel
<b>Input Cable Type</b>	(H05RN-F) 3 CORE rubberised cable (OD: 7mm)

### LED DRIVER

Driver	Input
N/A (integrated SELV driver)	220-240V

### ACCESSORIES

<b>JB5</b>	Gel filled waterproof connector	Sold Separately
<b>GH220</b>	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
<b>GS220</b>	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately

40°