



11.4W

11.4W



Coastal protected

IP65

IP65 ideal for outdoor areas

SL240 Mains

Mains voltage LED twin bar spike light

Features

| | |
|------------------------|-------------|
| IP rating | IP65 |
| CSP Switchable | Single CCT |
| Tiltable | 90° |
| LED Lifetime | L70 70,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM3 |
| Rotation Angle | 330° |

Installation Information

| | |
|-----------------------------|--|
| Input | 220-240V AC |
| Maximum Ambient Temperature | 35°C |
| Weight | SL240B: 1584g SL240D: 2700g SL240Z: 1414g |
| Inrush Current | 120A 37ms |
| Construction Material | Anodised aluminium Stainless Steel 316 |
| UK Bathroom Zone | N/A |
| SELV | Yes |
| Electric Class (1, 2, 3) | 1 |
| Earth Leakage | 0.1mA |
| Suitable for coastal areas | Yes |

Guarantee

Warranty 7 years

Features & benefits

- Adjustable bar-mounted twin heads, ideal for discreet illumination of shrubbery, trees and other landscape features
- Easily ground mounted with two spikes and single cable for quick installation
- Elegant and discreet black and bronze finishes
- Mains voltage for easy installation
- Highly efficiency of 93lm/W

Photometrics @ 25°C

| Product Code | Finish | W | Colour | Beam | lm | lm/W | Lx @ 1m | Energy |
|--------------|---------------------------|-------|--------|------|------|------|---------|--------|
| SL240ZWB27 | Bronze anodised aluminium | 11.4W | 2700K | 40° | 1030 | 2x90 | 2x1171 | AIG E |
| SL240ZWB30 | Bronze anodised aluminium | 11.4W | 3000K | 40° | 1040 | 2x91 | 2x1182 | AIG E |
| SL240BWB27 | Black anodised aluminium | 11.4W | 2700K | 40° | 1030 | 2x90 | 2x1171 | AIG E |
| SL240BWB30 | Black anodised aluminium | 11.4W | 3000K | 40° | 1040 | 2x91 | 2x1182 | AIG E |
| SL240DWB30 | Stainless steel | 11.4W | 3000K | 40° | 1040 | 2x91 | 2x1182 | AIG E |

Wiring Information

| | |
|-------------------------|---|
| Cable / Flying Lead | 3m H05RN-F rubberised cable (outside diameter: 7mm) |
| Type of Wiring Required | Parallel |
| Input Cable Type | (H05RN-F) 3 CORE rubberised cable (OD: 7mm) |

LED Driver

| Driver | Input | SELV | Dimming | Bathroom Zone |
|------------------------------|----------|------|---------|---------------|
| N/A (integrated SELV driver) | 220-240V | Yes | No | N/A |

Accessories

| | | |
|-------|--|-----------------|
| JB5 | Gel filled waterproof connector | Sold Separately |
| GH220 | Simple hood to reduce glare whilst maintaining a good light distribution | Sold Separately |
| GS220 | Simple hood to reduce glare whilst maintaining a good light distribution | Sold Separately |

