

- 4.4W** or **9.2W** 4.4W at 350mA or 9.2W at 700mA
- Coastal protected**
- IP65** IP65 ideal for outdoor areas

SL240

Low voltage LED twin bar spike light

Features

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	90°
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	330°

Installation Information

Input	350mA / 700mA
Maximum Ambient Temperature	35°C
Weight	SL240B: 1576g SL240D: 2600g SL240Z: 1401g
Inrush Current	N/A
Construction Material	Anodised aluminium Stainless Steel 316
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Adjustable bar-mounted twin heads, ideal for discreet illumination of shrubbery, trees and other landscape features
- Easily ground mounted with two spikes and single cable for quick installation
- Elegant and discreet black and bronze finishes
- Highly efficiency of 114lm/W
- Discreet cabling
- Additional accessories also available such as hoods and snoots

Photometrics @ 25°C

Product Code	Finish	Colour	Beam	350mA				700mA				Energy
				W	lm	lm/W	lx@ 1m	W	lm	lm/W	lx@ 1m	
SL240ZWBX27	Bronze anodised aluminium	2700K	40°	4.4W	580	135	2 x 659	9.2W	1030	111	2 x 1171	A B E
SL240ZWBX30	Bronze anodised aluminium	3000K	40°	4.4W	600	140	2 x 682	9.2W	1040	112	2 x 1182	A B E
SL240BWBX27	Black anodised aluminium	2700K	40°	4.4W	580	135	2 x 659	9.2W	1030	111	2 x 1171	A B E
SL240BWBX30	Black anodised aluminium	3000K	40°	4.4W	600	140	2 x 682	9.2W	1040	112	2 x 1182	A B E
SL240DWBX27	Stainless steel	2700K	40°	4.4W	580	135	2 x 659	9.2W	1030	111	2 x 1171	A B E
SL240DWBX30	Stainless steel	3000K	40°	4.4W	600	140	2 x 682	9.2W	1040	112	2 x 1182	A B E

Wiring Information


Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	(H05RN-F) 2 CORE rubberised cable (OD: 6mm)

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	2
PLU/700 3-9	220-240V	Yes	No	1	1	2
PSIP70036W	220-240V	Yes	No	1	2	3

Accessories

JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately



GS220

Simple hood to reduce glare whilst maintaining a good light distribution

Sold Separately



collingwood

This product brings an extra level of elegance to the landscape lighting range that can be easily installed as part of any exterior design. The Twin Bar Spike is a low-level bar with two rotatable LED heads mounted on a single bar, requiring only a single cable connection. Perfect for up-lighting trees, shrubs and facades, the bar has two spikes which are inserted into the ground or in planters and pots and can be easily moved and adjusted as required. The low-lying horizontal design of the Twin Bar Spike means it can be concealed, so only the dramatic effect of the light is seen, not the fitting itself. Features include IP65 rating for outdoor use, efficacy of 144lm/W, tiltable up to 90 degree and rotatable up to 330 degree. There are also straight to mains and low voltage options, three colour temperatures to choose from and a bronze finish version. A seven-year warranty is also available. Upgrade your light with low glare hoods and snoots.