



SL240

Low voltage LED twin bar spike light

4.4W
or
9.2W

4.4W at 350mA or 9.2W at 700mA



Coastal protected

IP65

IP65 ideal for outdoor areas

Features

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	90°
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	330°

Installation Information

Input	350mA / 700mA
Maximum Ambient Temperature	35°C
Weight	SL240B: 1576g SL240D: 2600g SL240Z: 1401g
Inrush Current	N/A
Construction Material	Anodised aluminium Stainless Steel 316
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Adjustable bar-mounted twin heads, ideal for discreet illumination of shrubbery, trees and other landscape features
- Easily ground mounted with two spikes and single cable for quick installation
- Elegant and discreet black and bronze finishes
- Highly efficiency of 114lm/W
- Discreet cabling
- Additional accessories also available such as hoods and snoots

Photometrics @ 25°C

Product Code	Finish	Colour	Beam	350mA				700mA				Energy
				W	lm	lm/W	lx@ 1m	W	lm	lm/W	lx@ 1m	
SL240ZWBX30	Bronze anodised aluminium	3000K	40°	4.4W	600	140	2 x 682	9.2W	1040	112	2 x 1182	A E
SL240BWBX27	Black anodised aluminium	2700K	40°	4.4W	580	135	2 x 659	9.2W	1030	111	2 x 1171	A E
SL240BWBX30	Black anodised aluminium	3000K	40°	4.4W	600	140	2 x 682	9.2W	1040	112	2 x 1182	A E
SL240DWBX27	Stainless steel	2700K	40°	4.4W	580	135	2 x 659	9.2W	1030	111	2 x 1171	A E

Wiring Information

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	(H05RN-F) 2 CORE rubberised cable (OD: 6mm)

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	2
PLU/700 3-9	220-240V	Yes	No	1	1	2
PSIP70036W	220-240V	Yes	No	1	2	3

Accessories

JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
GS220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately

