
Spike lights specification sheet





SL240

Low voltage LED twin bar spike light

Features					
IP rating	IP65				
CSP Switchable	Single CCT				
Tiltable	90°				
LED Lifetime	L70 70,000h				
Colour Rendering Index	CRI>80				
Colour Consistency	SDCM3				
Rotation Angle	330°				

Installation Information					
Input	350mA / 700mA				
Maximum Ambient Temperature	35°C				
Weight	SL240B: 1576g SL240D:				
weight	2600g SL240Z: 1401g				
Inrush Current	N/A				
Construction Material	Anodised aluminium				
Construction Material	Stainless Steel 316				
UK Bathroom Zone	N/A				
SELV	N/A				
Electric Class (1, 2, 3)	3				
Earth Leakage	N/A				

Yes

Suitable for coastal areas

Photometrics @ 25°C

Product Code	Finish	Colour	Beam	W	lm	lm/W	lx @	W	lm	lm/W	lx @	Energy
				350mA			1m	700mA			1m	
SL240ZWBX30	Bronze anodised aluminium	3000K	40°	4.4W	600	140	2 x 682	9.2W	1040	112	2 x 1182	Å E
SL240BWBX27	Black anodised aluminium	2700K	40°	4.4W	580	135	2 x 659	9.2W	1030	111	2 x 1171	A E
SL240BWBX30	Black anodised aluminium	3000K	40°	4.4W	600	140	2 x 682	9.2W	1040	112	2 x 1182	A E
SL240DWBX27	Stainless steel	2700K	40°	4.4W	580	135	2 x 659	9.2W	1030	111	2 x 1171	A E

Wiring Information

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	(H05RN-F) 2 CORE rubberised cable (OD: 6mm)

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	2
PLU/700 3-9	220-240V	Yes	No	1	1	2
PSIP70036W	220-240V	Yes	No	1	2	3

Accessories

Accessories		
JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
GS220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately

C collingwood



4.4W at 350maA or 9.2W at 700mA



Coastal protected



IP65 ideal for outdoor areas

Guarantee

Warranty 7 years

Features & benefits

- Adjustable bar-mounted twin heads, ideal for discreet illumination of shrubbery, trees and other landscape features
- Easily ground mounted with two spikes and single cable for quick installation
- Elegant and discreet black and bronze finishes
- Highly efficiency of 114lm/W
- Discreet cabling
- Additional accessories also available such as hoods and snoots

