

4.4W or 9.2W 4.4W at 350mA or 9.2W at 700mA

Coastal protected

IP65 IP65 ideal for outdoor areas

WARRANTY

Warranty 7 years

FEATURES & BENEFITS

Adjustable bar-mounted twin heads, ideal for discreet illumination of shrubbery, trees and other landscape features

Easily ground mounted with two spikes and single cable for quick installation

Elegant and discreet black and bronze finishes

Highly efficiency of 114lm/W

Discreet cabling

Additional accessories also available such as hoods and snoots



SL240

Low voltage LED twin bar spike light

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tilttable	90°
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	330°

INSTALLATION INFORMATION

Input	350mA / 700mA
Maximum Ambient Temperature	35°C
Weight	SL240B: 1576g SL240D: 2600g SL240Z: 1401g
Inrush Current	N/A
Construction Material	Anodised aluminium Stainless Steel 316
UK Bathroom Zone	N/A
SELV	N/A
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	Colour	Beam	W	lm	lm/W	lx @ 1m	W	lm	lm/W	lx @ 1m	Energy
				350mA				700mA				
SL240ZWBX30	Bronze anodised aluminium	3000K	40°	4.4W	600	140	2 x 682	9.2W	1040	112	2 x 1182	
SL240BWBX30	Black anodised aluminium	3000K	40°	4.4W	600	140	2 x 682	9.2W	1040	112	2 x 1182	
SL240DWBX27	Stainless steel	2700K	40°	4.4W	580	135	2 x 659	9.2W	1030	111	2 x 1171	

WIRING INFORMATION

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	(H05RN-F) 2 CORE rubberised cable (OD: 6mm)

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PSIP70036W	220-240V	Yes	No	1	2	3

ACCESSORIES

JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
GS220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately