



Image coming soon

SL320A

3W LED spike light

Features		Installation Information	
IP rating	IP65	Input	350mA
CSP Switchable	Single CCT	Maximum Ambient Temperature	35°C
Tiltable	90°	Weight	1700g
LED Lifetime	L70 70,000h	Construction Material	Copper
Colour Rendering Index	CRI>70	UK Bathroom Zone	1
Colour Consistency	SDCM3	Electric Class (1, 2, 3)	3
Rotation Angle	No		

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m
SL320A F NW	Copper	3W	4000K	38°	310	103	705

Wiring Information

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PSIP3509W	220-240V	Yes	No	1	1	8
PSMD35039	220-240V	Yes	Yes (mains)	1	3	9

Accessories

JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors
PDC/GRID DIMMER	1-10V dimmer module
GH220	Simple hood to reduce glare whilst maintaining a good light distribution
G5220	Stylish, baffle-style snoot, perfect for creating a moonlighting effect

Sold Separately



Equivalent to 20W halogen

Long spike included for extra stability

Robust cable for outdoor use

Guarantee

Warranty 1 year

Features & benefits

- Available in copper

Patent Information

GB2487912 GB2512715