



collingwood

3W

Equivalent to 20W halogen

Long spike included for extra stability

Robust cable for outdoor use

SL320A

3W LED spike light

Features

IP rating	IP65
CSP Switchable	Single CCT
Tilttable	90°
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>70
Colour Consistency	SDCM3

Installation Information

Input	350mA
Maximum Ambient Temperature	35°C
Weight	1700g
Construction Material	Copper
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m
SL320A F NW	Copper	3W	4000K	38°	310	103	705

Wiring Information

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PSIP3509W	220-240V	Yes	No	1	1	8
PSMD35039	220-240V	Yes	Yes (mains)	1	3	9

Accessories

JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors
PDC/GRID DIMMER	1-10V dimmer module
GH220	Simple hood to reduce glare whilst maintaining a good light distribution
GS220	Stylish, baffle-style snoot, perfect for creating a moonlighting effect

Guarantee

Warranty 1 year

Features & benefits

- Available in copper