SL320A

3W LED spike light

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tiltable (°)	90
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>70
Colour Consistency	SDCM3
Rotation angle (°)	Fixed

INSTALLATION INFORMATION

 Input
 350mA DC

 Maximum Ambient Temperature
 35°C

 Weight
 1700g

 Construction Material
 Copper

 UK Bathroom Zone
 1

 Electric Class (1, 2, 3)
 III

PHOTOMETRICS @ 25°C

Product code	Finish	w	Colour	Beam	lm	lm/W	Lx @ 1m
SL320A F NW	Copper	ЗW	4000K	38°	310	103	705

WIRING INFORMATION

Cable / Flying Lead Type of Wiring Required 3m H05RN-F rubberised cable (outside diameter: 6mm) Series

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PSIP3509W	220-240V	Yes	No	1	1	8

ACCESSORIES

JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors	
PDC/GRID DIMMER	1-10V dimmer module	
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	
GS220	Stylish, baffle-style snoot, perfect for creating a moonlighting effect	Sold Separately

LIGHTING INNOVATION

Equivalent to 20W halogen

λ.

Long spike included for extra stability

Robust cable for outdoor use

WARRANTY

i

1 year

FEATURES & BENEFITS

vailable in copper

PATENT: GB2487912 GB2512715