



2.2W at 350mA or 4.6W at 700mA



Coastal protected



IP65 ideal for outdoor areas

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Single LED and lens combination for maximum efficiency and optimal light distribution

Choice of material finish to suit different styles

Choose from a range of hoods for reduced glare.



GH220B



GS220B

SL230 SINGLE HEAD

Low voltage single head LED spike light

FEATURES

| | |
|------------------------|------------------|
| IP rating | IP65 |
| CSP Switchable | Single CCT |
| Tilttable (°) | 90 |
| Dimmable Option | Driver dependent |
| LED Lifetime | L70 70,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM3 |
| Rotation angle (°) | 330 |

INSTALLATION INFORMATION

| | |
|-----------------------------|--------------------|
| Input | 350mA / 700mA DC |
| Maximum Ambient Temperature | 50°C |
| Weight | 1.05 |
| Inrush Current | N/A |
| Construction Material | Anodised aluminium |
| UK Bathroom Zone | N/A |
| SELV | N/A |
| Electric Class (1, 2, 3) | III |
| Earth Leakage | N/A |
| Suitable for coastal areas | Yes |

Photometrics @ 25°C

| Product Code | Finish | Colour | Beam | 350mA | | | | 700mA | | | | Energy |
|--------------|--------|--------|------|-------|-----|------|---------|-------|-----|------|---------|--------|
| | | | | W | lm | lm/W | lx @ 1m | W | lm | lm/W | lx @ 1m | |
| SLX2305HB30 | Black | 3000K | 40° | 2.2W | 300 | 136 | 682 | 4.6W | 520 | 113 | 1182 | |

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

| | |
|-------------------------|---|
| Cable / Flying Lead | 3m H05RN-F rubberised cable (outside diameter: 6mm) |
| Type of Wiring Required | Series |
| Input Cable Type | (H05RN-F) 2 CORE rubberised cable (OD: 6mm) |

LED DRIVER

| Driver | Input | SELV | Dimming | Bathroom Zone | Min | Max |
|--------------------------|----------|------|---------|---------------|-----|-----|
| DRV150700 (all settings) | 220-240V | Yes | No | N/A | | |
| DRV350700TD (700mA) | 220-240V | Yes | Yes | N/A | | |
| PSIP70018W | 220-240V | Yes | No | 1 | 1 | 3 |

ACCESSORIES

| | | |
|-----------------|--|-----------------|
| JB2 / JB4 / JB6 | Waterproof junction box / Gel filled waterproof connectors | Sold Separately |
| GH220 | Simple hood to reduce glare whilst maintaining a good light distribution | Sold Separately |
| GS220 | Simple hood to reduce glare whilst maintaining a good light distribution | Sold Separately |

BEAM ANGLE: 40°

