


4.8W Ideal for accent lighting with 4.8W/m

IP20 Ideal for living room and hallways with IP20 rating

 Quick and easy installation with 3M self-adhesive backing

WARRANTY

Warranty 3 years

FEATURES & BENEFITS

- Driver included
- Excellent for accent lighting
- Cut points every 100mm
- 3M self-adhesive backing for secure and easy installation
- Supplied in a resealable, antistatic bag to protect during transit



SP50

IP20 LED strip pack and driver




FEATURES

IP rating	IP20
CSP Switchable	Single CCT
Dimmable Option	Driver dependent
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
Self-Adhesive Backing	Yes
Bespoke Lengths	No
Strip type	Flexible tape

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	53g per meter
Construction Material	Flexible tape
UK Bathroom Zone	2
Electric Class (1, 2, 3)	3
Maximum Running Length	5 m

PHOTOMETRICS @ 25°C

Product code	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
SP5040	5m reel 60 LED's/m	4.8W/m	4000K	120°	490	102	161	
SP5030	5m reel 60 LED's/m	4.8W/m	3000K	120°	450	94	148	
SP5027	5m reel 60 LED's/m	4.8W/m	2700K	120°	430	90	141	

WIRING INFORMATION

Cable / Flying Lead	Supplied with a minimum of 200mm flying lead from one end
Type of Wiring Required	Parallel

LED DRIVER

Driver	Input	SELV	Dimming	Min	Max
PS3024B	220-240V	Yes	Yes (with PDCINT1-10V)	-	5m

ACCESSORIES

LED STRIP PROFILE RANGE	Profile range to house adhesive strip	Sold Separately
PDCINT1-10V	1-10V dimming interface for use with 24V LED drivers	Sold Separately

5m/100mm



 8mm