



## SP50

IP20 LED strip pack and driver

### Features

IP rating	IP20
CSP Switchable	Single CCT
Dimmable Option	Driver dependent
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
Self-Adhesive Backing	Yes
Bespoke Lengths	No
Strip type	Flexible tape

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	53g per meter
Construction Material	Flexible tape
UK Bathroom Zone	2
Electric Class (1, 2, 3)	3
Maximum Running Length	5 m

### Photometrics @ 25°C

Product Code	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
SP5040	5m reel 60 LED's/m	4.8W/m	4000K	120°	490	102	161	
SP5030	5m reel 60 LED's/m	4.8W/m	3000K	120°	450	94	148	
SP5027	5m reel 60 LED's/m	4.8W/m	2700K	120°	430	90	141	

### Wiring Information

Cable / Flying Lead	Supplied with a minimum of 200mm flying lead from one end
Type of Wiring Required	Parallel

### LED Driver

Driver	Input	SELV	Dimming	Min	Max
PS3024B	220-240V	Yes	Yes (with PDCINTI 1-10V)	-	5m

### Accessories

LED STRIP PROFILE RANGE	Profile range to house adhesive strip	Sold Separately
PDCINTI-10V	1-10V dimming interface for use with 24V LED drivers	Sold Separately



collingwood



Ideal for accent lighting with 4.8W/m



Ideal for living room and hallways with IP20 rating



Quick and easy installation with 3M self-adhesive backing

### Guarantee

Warranty 3 years

### Features & benefits

- Driver included
- Excellent for accent lighting
- Cut points every 100mm
- 3M self-adhesive backing for secure and easy installation
- Supplied in a resealable, antistatic bag to protect during transit

5m/100mm

