



High efficacy of 138lm/W



Sensor kit includes junction box and counter weight



Emergency option available

Springbok Lite

High Bay Sbok Lite, 80W 11K lm, Non-Dim, 4000K

Features

| | |
|------------------------|---------------------------------------|
| IP rating | IP65 |
| IK rating | IK08 |
| CSP Switchable | Single CCT |
| Sensor Option | Microwave & Daylight with accessories |
| Dimmable Option | No |
| LED Lifetime | L70 54,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM5 |
| Emergency Option | Yes |

Installation Information

| | |
|-----------------------------|---|
| Input | 220-240V AC |
| Maximum Ambient Temperature | -20°C - 40°C |
| Weight | 1.60kg |
| Inrush Current | 100A 0.42ms |
| Construction Material | ADC12 aluminium alloy tempered glass |
| Electric Class (1, 2, 3) | 1 |
| Install Connector Type | Flying lead |
| UK Building Regulations | Part P |
| UK Protection | Surge Protection 6KV |
| Mounting Options | Jack Chain, Surface Bracket or Rod Mount |

Guarantee

| | |
|------------------|---------|
| Warranty | 4 years |
| Battery Warranty | 2 years |
| On-Site Warranty | 2 years |

Features & benefits

- Economical high bay for fast return on investment
- Easy to add microwave sensor kit includes junction box and counter weight
- On/off control with time delay and daylight switching (8-15 metres max)
- Suitable for jack chain, M10 drop rod or catenary wire suspension
- Pre-wired with 1.5M of H05RN-F cable for ease and speed of installation
- Replaceable driver for easy maintenance
- IK08 for robust impact protection

Photometrics @ 25°C

| Product Code | Finish | Type | W | Colour | Beam | lm | lm/W | EM lm | Energy |
|--------------|-----------------------|-----------|-----|--------|------|-------|------|-------|--------|
| HBLIN | Matt black RAL9017 | Standard | 80W | 4000K | 110° | 11000 | 138 | 530 | |
| HBLINEM | Matt black RAL9017 | Emergency | 80W | 4000K | 110° | 11000 | 138 | 530 | |

Wiring Information

| | |
|-------------------------|--|
| Cable / Flying Lead | 1.5m H05RN-F 3x1.0mm ² Ø7mm |
| Type of Wiring Required | Parallel |

Accessories

| | | |
|----------|---|-----------------|
| HBLMWS | High Bay Sbok Lite, Microwave sensor kit inc junction box and counterweight | Sold Separately |
| HBREM | High Bay Sbok Lite, Remote control for commissioning HBLMWS | Sold Separately |
| HBLIREFR | High Bay Sbok Lite, 80W 80-degree refractor | Sold Separately |
| HBBRA | Bracket Mount for Standard Springbok Lite | Sold Separately |
| HBBRAEXT | Extended Bracket Mount for Standard Springbok Lite | Sold Separately |

