Battens specification sheet



# Bolt-On PIR

On/off PIR sensor with Lux level switch

Features		Installation Infor	Installation Information	
IP rating	IP65	Weight	82g	
Sensor Option	PIR	Construction Material	Polycarbonate	
		UK Bathroom Zone	N/A	
		Install Connector Type	Flying lead	
		Connection Output	DC Plug and Play	
			Connector	

Borealis

Caiman

Lentus

## Photometrics @ 25°C

Product Code	Finish	Туре	w		
SSENBPSTWH	White	Install height of 2-6M	500W		
Accessories					
Borealis Batten	All variants		Sold Separately		
Caiman Anti-Corrosive	All variants		Sold Separately		
Lentus Lowbay	All variants		Sold Separately		



Compatible with:

BOREALIS Batten

CAIMAN Anti-Corrosive

### Guarantee

Warranty

#### У


### **Features & benefits**

- LENTUS Lowbay
- Suitable for use at heights of 2.5 to 6.0 metres

5 years

- Fast 4-minute conversion time
- M20 interface for easy installation
- Delay time can be adjusted from 30 seconds up to 30 minutes
- Lux level switch can be adjusted from 3 lux to 300 lux





136mm		
$\bigcirc$		33mm
	 	28mm

in collingwoodlighting or collingwoodled