

SALVUS EMERGENCY BULKHEAD

145lm, emergency bulkhead

FEATURES

IP rating	IP65		
IK rating	IK07		
CSP Switchable	Single CCT		
Colour Rendering Index	CRI>80		
Maintained / Non-Maintained	Maintained, Non-		
	Maintained		

INSTALLATION INFORMATION

Input	220-240V AC		
Maximum Ambient Temperature	45°C		
Weight	0.54Kg		
Inrush Current	20A		
Construction Material	Lens PC housing ABS		
Electric Class (1, 2, 3)			
Battery	LiFePO4		
Install Connector Type	Push-fit terminal, loop-		
	in/loop-out		
Mounting Options	Ceiling, wall, suspended,		
	BESA & conduit M20		
Viewing distance	18		

PHOTOMETRICS @ 25°C

Product code	Finish	Туре	W	Colour	Beam	lm
EMBH145M	White	Manual-test	3.0W	6500K	120°	145

WIRING INFORMATION

Cable / Flying Lead	0.5 to 1.0mm ²
Type of Wiring Required	Parallel

ACCESSORIES

N/A (No Accessories required)



LIGHTING INNOVATION



LiFeP04 battery available



Self-test or Manual test available



IP65 suitable for outdoor environments

WARRANTY

Warranty

2 years

FEATURES & BENEFITS

By simply connecting the cables to the push-fit terminals, terminals allow for both maintained and non-maintained usage

Has three M20 entry knock-outs (one on each side and one in the bottom), and rear BESA box fixing points

Diffuser is rugged and made of polycarbonate

Viewing distance of 18m

Complying with ISO 3864-1, and proud member of the ICEL

Ideal for open areas, escape routes, for general illumination or as an exit sign

Adhesive legend is supplied and divided in five parts