



LiFePO4 battery available



Self-test or Manual test available



IP65 suitable for outdoor environments

WARRANTY

Warranty

2 years

FEATURES & BENEFITS

By simply connecting the cables to the push-fit terminals, terminals allow for both maintained and non-maintained usage

Has three M20 entry knock-outs (one on each side and one in the bottom), and rear BESA box fixing points

Diffuser is rugged and made of polycarbonate

Viewing distance of 18m

Complying with ISO 3864-1, and proud members of the ICEL

Ideal for open areas, escape routes, for general illumination or as an exit sign

Adhesive legend is supplied and divided in five parts



SALVUS EMERGENCY BULKHEAD

145lm, emergency bulkhead

FEATURES

IP rating	IP65
IK rating	IK07
CSP Switchable	Single CCT
Colour Rendering Index	CRI>80

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	45°C
Weight	0.65Kg
Inrush Current	20A
Construction Material	Lens PC housing ABS
Electric Class (1, 2, 3)	2
Battery	LiFePO4
Install Connector Type	Push-fit terminal, loop-in/loop-out
Mounting Options	Ceiling, wall, suspended, BESA & conduit M20
Viewing distance	18

PHOTOMETRICS @ 25°C

Product code	Type	Colour	Beam
EMBH145M	Manual-test	6500K	120°
EMBH145S	Self-test	6500K	120°

WIRING INFORMATION

Cable / Flying Lead	0.5 to 1.0mm²
Type of Wiring Required	Parallel

ACCESSORIES

N/A (No Accessories required)