



LiFePO4 battery available



Self-test or Manual test available



IP65 suitable for outdoor environments

Salvus Emergency Bulkhead

145lm, emergency bulkhead

Features

IP rating	IP65
IK rating	IK07
CSP Switchable	Single CCT
Colour Rendering Index	CRI>80

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	45°C
Weight	0.65Kg
Inrush Current	20A
Construction Material	Lens PC housing ABS
Electric Class (1, 2, 3)	2
Battery	LiFePO4
Install Connector Type	Push-fit terminal, loop-in/loop-out
Mounting Options	Ceiling, wall, suspended, BESA & conduit M20
Viewing distance	18

Guarantee

Warranty 2 years

Features & benefits

- By simply connecting the cables to the push-fit terminals, terminals allow for both maintained and non-maintained usage
- Has three M20 entry knock-outs (one on each side and one in the bottom), and rear BESA box fixing points
- Diffuser is rugged and made of polycarbonate
- Viewing distance of 18m
- Complying with ISO 3864-1, and proud members of the ICEL
- Ideal for open areas, escape routes, for general illumination or as an exit sign
- Adhesive legend is supplied and divided in five parts

Photometrics @ 25°C

Product Code	Type	Colour	Beam
EMBHI45M	Manual-test	6500K	120°
EMBHI45S	Self-test	6500K	120°


Wiring Information

Cable / Flying Lead	0.5 to 1.0mm ²
Type of Wiring Required	Parallel


Accessories

N/A (No Accessories required)

355mm



110mm



56mm