



## SALVUS EMERGENCY EXIT BLADE

50lm, emergency exit blade

### FEATURES

<b>IP rating</b>	IP20
<b>IK rating</b>	IK08
<b>CSP Switchable</b>	Single CCT
<b>Colour Rendering Index</b>	CRI>80

### INSTALLATION INFORMATION

<b>Input</b>	220-240V AC
<b>Maximum Ambient Temperature</b>	45°C
<b>Weight</b>	0.9Kg
<b>Inrush Current</b>	10.3A 100ms
<b>Construction Material</b>	Lens PC housing PC
<b>Electric Class (1, 2, 3)</b>	2
<b>Battery</b>	LiFePO4
<b>Install Connector Type</b>	Push-fit terminal, loop-in/loop-out
<b>Mounting Options</b>	Ceiling, wall & suspended
<b>Viewing distance</b>	30

### PHOTOMETRICS @ 25°C

Product code	Type	Colour	Beam
<b>EMBL30M</b>	Manual-test	6500K	120°
<b>EMBL30S</b>	Self-test	6500K	120°

### WIRING INFORMATION

<b>Cable / Flying Lead</b>	Screwless terminals, up to 0.75mm <sup>2</sup>
<b>Type of Wiring Required</b>	Parallel

### ACCESSORIES

<b>EMBLUP</b>	Pictogram Arrow UP.	Sold Separately
<b>EMBLDO</b>	Pictogram Arrow DOWN.	Sold Separately
<b>EMBLRI</b>	Pictogram Arrow RIGHT.	Sold Separately
<b>EMBLLE</b>	Pictogram Arrow LEFT.	Sold Separately
<b>EMBLSK</b>	Suspension Kit (2x 1m cable + fixings)	Sold Separately



LiFePO4 battery available



Self-test or Manual test available



Auxiliary floor illumination to light areas under fitting

### WARRANTY

Warranty

3 years

### FEATURES & BENEFITS

Maintained, so it can be turned on/off when the mains is on

Has three M20 entry knock-outs (one on each side and one in the bottom), and rear BESA box fixing points

Housing is rugged and made of polycarbonate

30m viewing distance allowing it to be assembled in different room dimensions

Complying with ISO 3864-1, and proud members of the ICEL