



LiFePO4 battery available



Self-test or Manual test available



Auxiliary floor illumination to light areas under fitting

## WARRANTY

Warranty

2 years

## FEATURES & BENEFITS

By simply connecting the cables to the push-fit terminals, terminals allow for both maintained and non-maintained usage

NiCd is a well-proven and widely used technology

Housing is rugged and made of polycarbonate

35m viewing distance allowing it to be assembled in many different room dimensions

Complying with ISO 3864-1, and proud members of the ICEL

# SALVUS EMERGENCY EXIT BOX

47lm, emergency exit box

## FEATURES

<b>IP rating</b>	IP20
<b>IK rating</b>	IK08
<b>CSP Switchable</b>	Single CCT
<b>Colour Rendering Index</b>	CRI>80
<b>Maintained / Non-Maintained</b>	Maintained, Non-Maintained

## INSTALLATION INFORMATION

<b>Input</b>	220-240V AC
<b>Maximum Ambient Temperature</b>	0°C - 45°C
<b>Weight</b>	0.6Kg
<b>Inrush Current</b>	12A 56ms
<b>Construction Material</b>	Lens PC housing PC
<b>Electric Class (1, 2, 3)</b>	II
<b>Battery</b>	NiCd
<b>Install Connector Type</b>	Push-fit terminal, loop-in/loop-out
<b>Mounting Options</b>	Wall
<b>Viewing distance</b>	35

## PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm
EMBX35M	White	Manual-test	3.5W	6500K	N/A	47

## WIRING INFORMATION

<b>Cable / Flying Lead</b>	0.5 to 1.0mm <sup>2</sup>
<b>Type of Wiring Required</b>	Parallel

## ACCESSORIES

<b>EMBXUP</b>	Pictogram Arrow UP.	Sold Separately
<b>EMBXRI</b>	Pictogram Arrow RIGHT.	Sold Separately
<b>EMBXLE</b>	Pictogram Arrow LEFT.	Sold Separately