



## Salvus Emergency Exit Box

47lm, emergency exit box

### Features

IP rating	IP20
IK rating	IK08
CSP Switchable	Single CCT
Colour Rendering Index	CRI>80

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	0°C - 45°C
Weight	0.6Kg
Inrush Current	12A 56ms
Construction Material	Lens PC housing PC
Electric Class (1, 2, 3)	2
Battery	NiCd
Install Connector Type	Push-fit terminal, loop-in/loop-out
Mounting Options	Wall
Viewing distance	35

### Photometrics @ 25°C

Product Code	Type	Colour	Beam
EMBX35M	Manual-test	6500K	N/A
EMBX35S	Self-test	6500K	N/A

### Wiring Information

Cable / Flying Lead	0.5 to 1.0mm <sup>2</sup>
Type of Wiring Required	Parallel

### Accessories

EMBXUP	Pictogram Arrow UP.	Sold Separately
EMBXDO	Pictogram Arrow DOWN.	Sold Separately
EMBXRI	Pictogram Arrow RIGHT.	Sold Separately
EMBXLE	Pictogram Arrow LEFT.	Sold Separately



collingwood



LiFeP04 battery available



Self-test or Manual test available



Auxiliary floor illumination to light areas under fitting


### Guarantee

Warranty 2 years


### Features & benefits

- By simply connecting the cables to the push-fit terminals, terminals allow for both maintained and non-maintained usage
- NiCd is a well-proven and widely used technology
- Housing is rugged and made of polycarbonate
- 35m viewing distance allowing it to be assembled in many different room dimensions
- Complying with ISO 3864-1, and proud members of the ICEL

390.3mm



175.3mm



30mm

