



LiFePO4 battery available



Self-test or Manual test  
available



Auxiliary floor illumination to  
light areas under fitting

## WARRANTY

Warranty

2 years

## FEATURES & BENEFITS

By simply connecting the cables to the push-fit terminals, terminals allow for both maintained and non-maintained usage

NiCd is a well-proven and widely used technology

Housing is rugged and made of polycarbonate

35m viewing distance allowing it to be assembled in many different room dimensions

Complying with ISO 3864-1, and proud members of the ICEL

# SALVUS EMERGENCY EXIT BOX

47lm, emergency exit box

## FEATURES

IP rating	IP20
IK rating	IK08
CSP Switchable	Single CCT
Colour Rendering Index	CRI>80

## INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C - 45°C
Weight	0.6Kg
Inrush Current	12A 56ms
Construction Material	Lens PC housing PC
Electric Class (1, 2, 3)	II
Battery	NiCd
Install Connector Type	Push-fit terminal, loop-in/loop-out
Mounting Options	Wall
Viewing distance	35

## PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm
EMBX35M	White	Manual-test	3.5W	6500K	N/A	47

## WIRING INFORMATION

Cable / Flying Lead	0.5 to 1.0mm <sup>2</sup>
Type of Wiring Required	Parallel

## ACCESSORIES

EMBXUP	Pictogram Arrow UP.	Sold Separately
EMBXRI	Pictogram Arrow RIGHT.	Sold Separately
EMBXLE	Pictogram Arrow LEFT.	Sold Separately