



LiFeP04 battery available



Self-test or Manual test available



Auxiliary floor illumination to light areas under fitting

Salvus Emergency Exit Box

47lm, emergency exit box

Features

IP rating	IP20
IK rating	IK08
CSP Switchable	Single CCT
Colour Rendering Index	CRI>80

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	0°C - 45°C
Weight	0.6Kg
Inrush Current	12A 56ms
Construction Material	Lens PC housing PC
Electric Class (1, 2, 3)	2
Battery	NiCd
Install Connector Type	Push-fit terminal, loop-in/loop-out
Mounting Options	Wall
Viewing distance	35

Guarantee

Warranty 2 years

Photometrics @ 25°C

Product Code	Type	W	Colour	Beam	lm
EMBX35M	Manual-test	3.5W	6500K	N/A	47
EMBX35S	Self-test	3.5W	6500K	N/A	47

Wiring Information

Cable / Flying Lead	0.5 to 1.0mm ²
Type of Wiring Required	Parallel

Accessories

EMBXUP	Pictogram Arrow UP.	Sold Separately
EMBXDO	Pictogram Arrow DOWN.	Sold Separately
EMBXRI	Pictogram Arrow RIGHT.	Sold Separately
EMBXLE	Pictogram Arrow LEFT.	Sold Separately

Features & benefits

- By simply connecting the cables to the push-fit terminals, terminals allow for both maintained and non-maintained usage
- NiCd is a well-proven and widely used technology
- Housing is rugged and made of polycarbonate
- 35m viewing distance allowing it to be assembled in many different room dimensions
- Complying with ISO 3864-1, and proud members of the ICEL

