

SALVUS EMERGENCY TWIN SPOT

400lm, self test emergency twin spot

FEATURES

| IP rating | IP65 |
|-----------------------------|----------------|
| IK rating | IK08 |
| CSP Switchable | Single CCT |
| Colour Rendering Index | CRI>80 |
| Maintained / Non-Maintained | Non-Maintained |

INSTALLATION INFORMATION

| Input | 220-240V AC | |
|-----------------------------|--------------------------|--|
| Maximum Ambient Temperature | 0°C - 45°C | |
| Weight | 1Kg | |
| Inrush Current | 10.8A 84⊠s | |
| Construction Material | Lens PC housing PC | |
| Electric Class (1, 2, 3) | II | |
| Battery | LiFePO4 | |
| Install Connector Type | Push-fit terminal, loop- | |
| | in/loop-out | |
| Mounting Options | Wall | |
| Viewing distance | 0 | |

PHOTOMETRICS @ 25°C

| Product code | Finish | Туре | W | Colour | Beam | lm |
|--------------|--------|-----------|------|--------|------|-----|
| EMTW400S | White | Self-test | 4.8W | 6500K | 105° | 400 |

WIRING INFORMATION

| Cable / Flying Lead | 0.5 to 1.0mm ² |
|-------------------------|---------------------------|
| Type of Wiring Required | Parallel |

ACCESSORIES

N/A (No Accessories required)



LIGHTING INNOVATION



LiFeP04 battery available



Self-test available



IP65 suitable for outdoor environments

WARRANTY

Warranty

3 years

FEATURES & BENEFITS

Adjustable LED heads allow beam aiming

A rugged robust polycarbonate lens and housing

Charging Time = 24h

IEC reference standard - EN 60598-2-22, EN 62034