



LiFePO4 battery available



Self-test available



IP65 suitable for outdoor environments

WARRANTY

Warranty

3 years

FEATURES & BENEFITS

Adjustable LED heads allow beam aiming

A rugged robust polycarbonate lens and housing

Charging Time = 24h

IEC reference standard - EN 60598-2-22, EN 62034



SALVUS EMERGENCY TWIN SPOT

400lm, self test emergency twin spot

FEATURES

IP rating	IP65
IK rating	IK08
CSP Switchable	Single CCT
Colour Rendering Index	CRI>80

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C - 45°C
Weight	1Kg
Inrush Current	10.8A 84ms
Construction Material	Lens PC housing PC
Electric Class (1, 2, 3)	2
Battery	LiFePO4
Install Connector Type	Push-fit terminal, loop-in/loop-out
Mounting Options	Wall
Viewing distance	0

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm
EMTW400S	White	Self-test	4.8W	6500K	105°	400

WIRING INFORMATION

Cable / Flying Lead	0.5 to 1.0mm ²
Type of Wiring Required	Parallel

ACCESSORIES

N/A (No Accessories required)
