



LiFePO4 battery



Battery Temperature
Monitored



DALI-2 Addressable

WARRANTY

Warranty	5 years
Battery Warranty	5 years

FEATURES & BENEFITS

Compliant with ISO 7010 & 3864

Housing is rugged and made of polycarbonate

Legend Kit included

Self-test function can be easily disabled by removing green 2-pin jumper connector



SALVUS EXIT BLADE

24M Viewing Distance Exit Sign

FEATURES

IP rating	IP20
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Emergency Option	Yes, Self and DALI-2 Test
Maintained / Non-Maintained	Maintained

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C-40°C
Weight	EMBLWDP: 580g, EMBLRWD: 580g
Inrush Current	EMBLWDP: 4A 1ms, EMBLRWD: 4A 1ms
Construction Material	PC Housing
Electric Class (1, 2, 3)	I
Battery	EMBLWDP: LiFePO4 3.2V 1000mAh, EMBLRWD: LiFePO4 3.2V 1000mAh,
UK Building Regulations	N/A
Mounting Options	Surface
Viewing distance	24

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	EM lm
EMBLWDP	White	DALI-2	2.5W	6500K	180	34	34

WIRING INFORMATION

Cable / Flying Lead	N/A
Type of Wiring Required	Parallel

ACCESSORIES

EMBLWSKP	Salvus Exit Blade 24M, White, Susp Kit	Sold Separately
EMBLWSRP	Salvus Exit Blade 24M, White, Susp Rod Kit	Sold Separately
EMBLWWP	Salvus Exit Blade 24M, White, Wall Bracket	Sold Separately

