



LiFePO4 battery



Battery Temperature
Monitored



DALI-2 Addressable, Manual
& Self Test Option

WARRANTY

Warranty	5 years
Battery Warranty	5 years

FEATURES & BENEFITS

- Compliant with ISO 7010 & 3864
- Housing is rugged and made of polycarbonate
- Push bar illuminance for final exit
- Legend Kit included
- Self-test function can be easily disabled by removing green 2-pin jumper connector



SALVUS EXIT BOX

32M Viewing Distance Final Exit Sign

FEATURES

IP rating	IP65
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Emergency Option	Yes, Manual & Self-Test
Maintained / Non-Maintained	Maintained, Non-Maintained

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C-40°C
Weight	EMBXWMSHP: 1015g, EMBXWDHP: 1015g
Inrush Current	4.5A 63.5ms
Construction Material	Polycarbonate
Electric Class (1, 2, 3)	I
Battery	EMBXWMSHP: LiFePO4 3.2V 2000mAH, EMBXWDHP: LiFePO4 3.2V 2000mAH,
Install Connector Type	Push-fit terminal connector
UK Building Regulations	N/A
Mounting Options	Surface
Viewing distance	32

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	EM lm
EMBXWMSHP	White	Manual & Self Test	3W	6500K	50°	70	70
EMBXWDHP	White	DALI-2	3W	6500K	50°	70	70

WIRING INFORMATION

Type of Wiring Required	Parallel
-------------------------	----------

