



LiFePO4 battery



Battery Temperature Monitored



DALI-2 Addressable, Manual & Self Test Option

## SALVUS EXIT BOX

32M Viewing Distance Final Exit Sign

### FEATURES

<b>IP rating</b>	IP65
<b>IK rating</b>	IK08
<b>CSP Switchable</b>	Single CCT
<b>LED Lifetime</b>	L70 50,000h
<b>Emergency Option</b>	Yes, Manual & Self-Test
<b>Maintained / Non-Maintained</b>	Maintained, Non-Maintained

### INSTALLATION INFORMATION

<b>Input</b>	220-240V AC
<b>Maximum Ambient Temperature</b>	0°C-40°C
<b>Weight</b>	EMBXWMSHP: 360g, EMBXWDHP: 1015g
<b>Inrush Current</b>	4.5A 1ms
<b>Construction Material</b>	Polycarbonate
<b>Electric Class (1, 2, 3)</b>	I
<b>Battery</b>	EMBXWMSHP: LiFePO4 3.2V 2000mAH, EMBXWDHP: LiFePO4 3.2V 2000mAH,
<b>Install Connector Type</b>	Push-fit terminal connector
<b>UK Building Regulations</b>	N/A
<b>Mounting Options</b>	Surface
<b>Viewing distance</b>	32

### WARRANTY

Warranty	5 years
Battery Warranty	5 years

### FEATURES & BENEFITS

- Compliant with ISO 7010 & 3864
- Housing is rugged and made of polycarbonate
- Push bar illuminance for final exit
- Legend Kit included
- Self-test function can be easily disabled by removing green 2-pin jumper connector

### PHOTOMETRICS @ 25°C

Finish	Type	W	Colour	Beam	lm	EM lm
White	Manual & Self Test	3W	6500K	50°	70	70
White	DALI-2	3W	6500K	50°	70	70

### WIRING INFORMATION

<b>Type of Wiring Required</b>	Parallel
--------------------------------	----------

