



LiFePO4 battery



Battery Temperature  
Monitored



DALI-2 Addressable, Manual  
& Self Test Option

## WARRANTY

Warranty	5 years
Battery Warranty	5 years

## FEATURES & BENEFITS

- Compliant with ISO 7010 & 3864
- Housing is rugged and made of polycarbonate
- Push bar illuminance for final exit
- Legend Kit included
- Self-test function can be easily disabled by removing green 2-pin jumper connector



# SALVUS EXIT BOX

32M Viewing Distance Final Exit Sign

## FEATURES

IP rating	IP20
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Emergency Option	Yes, Manual & Self-Test

## INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C-40°C
Weight	635g
Inrush Current	4A 62.5ms
Construction Material	Polycarbonate & Steel
Electric Class (1, 2, 3)	1
Battery	LiFePO4 3.2V 1000mAH
Install Connector Type	Push-fit terminal connector
UK Building Regulations	N/A
Mounting Options	Surface
Viewing distance	32

## PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	EM lm
EMBXWMS	White	2.5W	6500K	93°	26	26

## WIRING INFORMATION

Type of Wiring Required	Parallel
-------------------------	----------

