



167lm/W

High efficacy of 167lm/W



Wattage Switchable
between 6W & 10W

IP66

IP66 suitable for warehouse
all applications

SALVUS MAX

High Output Emergency Bulkhead

FEATURES

IP rating	IP66
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Maintained / Non-Maintained	Non-Maintained

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C - 45°C
Weight	1.47kg
Inrush Current	6.8A 0.1ms
Construction Material	PC
Electric Class (1, 2, 3)	II
Battery	LiFePO4 6.4V 6.6Ah
Install Connector Type	Push-fit terminal, loop-in/loop-out
Mounting Options	Ceiling, wall, BESA & conduit M20

PHOTOMETRICS @ 25°C

Finish	Type	W	Colour	Beam	EM lm	Lx @ 1m
White	Manual-test	6W-10W	6500K	135°	1000-1500lm	204-306
White	Self-test	6W-10W	6500K	135°	1000-1500lm	204-306

WIRING INFORMATION

Cable / Flying Lead	0.75-4.0mm ²
Type of Wiring Required	Parallel

ACCESSORIES

Area Bay	Use as remote emergency solution to reduce light points required	Sold Separately
Caiman	Use as remote emergency solution to reduce light points required	Sold Separately
Borealis	Use as remote emergency solution to reduce light points required	Sold Separately

