



collingwood



High efficacy of 167lm/W



Wattage Switchable between 6W & 10W



IP66 suitable for warehouse all applications

## Salvus Max

Features		Installation Information	
IP rating	IP66	Input	220-240V AC
IK rating	IK08	Maximum Ambient Temperature	0°C - 45°C
CSP Switchable	Single CCT	Weight	1.47kg
LED Lifetime	L70 50,000h	Inrush Current	6.8A 0.1ms
Colour Rendering Index	CRI>80	Construction Material	PC
		Electric Class (1, 2, 3)	2
		Battery	LiFePO4 6.4V 6.6Ah
		Install Connector Type	Push-fit terminal, loop-in/loop-out
		Mounting Options	Ceiling, wall, BESA & conduit M20

### Guarantee

Warranty	4 years
Battery Warranty	2 years

### Features & benefits

- 1500lm output
- 15 metres mounting height, provides 1 lux (escape route) at floor level when using 29 metre spacings
- 25 metres mounting height, provides 0.5 (anti-panic) lux at floor level when using 40 metre spacings
- Lithium iron phosphate (LiFePO4) battery technology for long lifetime and fast charge times
- Captive screws for easy installation

### Photometrics @ 25°C

Product Code	Finish	Type	Colour	Beam	EM lm	Lx @ 1m
EMBMAX	White	Manual-test	6500K	135°	1000-1500lm	204-306
EMBMAXST	White	Self-test	6500K	135°	1000-1500lm	204-306

### Wiring Information

Cable / Flying Lead	0.75-4.0mm <sup>2</sup>
Type of Wiring Required	Parallel

### Accessories

Area Bay	Use as remote emergency solution to reduce light points required	Sold Separately
Caiman	Use as remote emergency solution to reduce light points required	Sold Separately
Borealis	Use as remote emergency solution to reduce light points required	Sold Separately

