



High efficacy of 167lm/W



Wattage Switchable between 6W & 10W



IP66 suitable for warehouse all applications

Salvus Max

High Output Emergency Bulkhead

Features

IP rating	IP66
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	0°C - 45°C
Weight	1.47kg
Inrush Current	6.8A 0.1ms
Construction Material	PC
Electric Class (1, 2, 3)	2
Battery	LiFePO4 6.4V 6.6Ah
Install Connector Type	Push-fit terminal, loop-in/loop-out
Mounting Options	Ceiling, wall, BESA & conduit M20

Guarantee

Warranty	4 years
Battery Warranty	2 years

Features & benefits

- 1500lm output
- 15 metres mounting height, provides 1 lux (escape route) at floor level when using 29 metre spacings
- 25 metres mounting height, provides 0.5 (anti-panic) lux at floor level when using 40 metre spacings
- Lithium iron phosphate (LiFePO4) battery technology for long lifetime and fast charge times
- Captive screws for easy installation

Photometrics @ 25°C

Product Code	Finish	Type	Colour	Beam	EM lm	Lx @ 1m
EMBMAX	White	Manual-test	6500K	135°	1000-1500lm	204-306
EMBMAXST	White	Self-test	6500K	135°	1000-1500lm	204-306

Wiring Information

Cable / Flying Lead	0.75-4.0mm ²
Type of Wiring Required	Parallel

Accessories

Area Bay	Use as remote emergency solution to reduce light points required	Sold Separately
Caiman	Use as remote emergency solution to reduce light points required	Sold Separately
Borealis	Use as remote emergency solution to reduce light points required	Sold Separately

