







SALVUS PIR BOLT-ON

FEATURES

IP rating	IP65
IK rating	IK07
Sensor Option	PIR

INSTALLATION INFORMATION

Input	220-240V AC
Weight	114g
Construction Material	PC
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	II
Install Connector Type	Flying lead

PHOTOMETRICS @ 25°C

Product code	Finish	Туре	W	EM lm	Lx @ 1m
PIRBOLT	White RAL9016	On-Off	0.5W	1	1
PIRBOLTDIM	White RAL9016	Step Dim	0.5W	1	1
PIRBOLTDIMR		Step Dim Remote	N/A		

ACCESSORIES

Borealis Batten	PIRBOLTDIM requires a 0-10V dimmable driver, PIRBOLT can be used with any driver	Sold Separately
Caiman Anti Corrosive	PIRBOLTDIM requires a 0-10V dimmable driver, PIRBOLT can be used with any driver	Sold Separately



LIGHTING INNOVATION

Compatiable with: BOREALIS, CAIMAN Anti-Corrosive, LENTUS

Suitable for use at heights of 2.5 to 6.0 metres



Quick and easy installation with M20 interface

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

Fast 4-minute conversion time

PIRBOLTDIM requires the luminaire to have a 0 0V driver

PIRBOLTDIMR - CR2025 battery not included



