



Compatible with: BOREALIS, CAIMAN Anti-Corrosive, LENTUS

Suitable for use at heights of 2.5 to 6.0 metres



Quick and easy installation with M20 interface

Salvus PIR Bolt-On

Features

| | |
|---------------|------|
| IP rating | IP65 |
| IK rating | IK07 |
| Sensor Option | PIR |

Installation Information

| | |
|--------------------------|-------------|
| Input | 220-240V AC |
| Weight | 82g |
| Construction Material | PC |
| UK Bathroom Zone | N/A |
| Electric Class (1, 2, 3) | 2 |
| Install Connector Type | Flying lead |

Guarantee

Warranty 5 years

Photometrics @ 25°C

| Product Code | Finish | Type | W | lm | lm/W | EM lm | Lx @ 1m |
|--------------|---------------|----------|------|----|------|-------|---------|
| PIRBOLT | White RAL9016 | On-Off | 0.5W | 1 | 1 | 1 | 1 |
| PIRBOLTDIM | White RAL9016 | Step Dim | 0.5W | 1 | 1 | 1 | 1 |

Features & benefits

- Fast 4-minute conversion time
- PIRBOLTDIM requires the luminaire to have a 0-10V driver
- PIRBOLTDIMR - CR2025 battery not included

Wiring Information

| | |
|-------------------------|--------------------------------|
| Cable / Flying Lead | 1.4m (2x 0.75mm ²) |
| Type of Wiring Required | Parallel |

Accessories

| | | |
|-----------------------|--|-----------------|
| Borealis Batten | PIRBOLTDIM requires a 0-10V dimmable driver, PIRBOLT can be used with any driver | Sold Separately |
| Caiman Anti Corrosive | PIRBOLTDIM requires a 0-10V dimmable driver, PIRBOLT can be used with any driver | Sold Separately |
| Lentus Lowbay | PIRBOLTDIM requires a 0-10V dimmable driver, PIRBOLT can be used with any driver | Sold Separately |

