

## SALVUS ROUTE

High Performance Emergency Spot

### FEATURES

<b>IP rating</b>	IP20
<b>IK rating</b>	IK04
<b>CSP Switchable</b>	Single CCT
<b>LED Lifetime</b>	L70 50,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Maintained / Non-Maintained</b>	Maintained, Non-Maintained

### INSTALLATION INFORMATION

<b>Input</b>	220-240V AC
<b>Maximum Ambient Temperature</b>	5°C - 45°C
<b>Weight</b>	180g
<b>Inrush Current</b>	3.04A
<b>Cut Out Size</b>	43-44
<b>Construction Material</b>	Polycarbonate
<b>Electric Class (1, 2, 3)</b>	II
<b>Battery</b>	LiFePO4 3.2V 1500mAh
<b>Install Connector Type</b>	Integrated terminals, loop-in/loop-out
<b>Mounting Options</b>	Recessed

### PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	EM lm	Lx @ 1m
<b>EMRWMAN</b>	White RAL9003	Manual-test	1W	6500K	165° / 160°x50°	130 Open - 120 Corridor	34 (Corridor) 27 (Open)
<b>EMRBST</b>	Black RAL9005	Self-test	1W	6500K	165° / 160°x50°	130 Open - 120 Corridor	34 (Corridor) 27 (Open)


### WIRING INFORMATION

<b>Cable / Flying Lead</b>	300mm long flying lead, H03VVH2-F 2x0.75mm <sup>2</sup>
<b>Type of Wiring Required</b>	Parallel

### ACCESSORIES

<b>Office</b>	Remote emergency lighting for mains lighting range	Sold Separately
<b>Education</b>	Remote emergency lighting for mains lighting range	Sold Separately
<b>Retail</b>	Remote emergency lighting for mains lighting range	Sold Separately
<b>Hotel &amp; Leisure</b>	Remote emergency lighting for mains lighting range	Sold Separately

**130lm/W** High efficacy of 130lm/W

 Quick and easy installation with loop-in/loop-out connector

**1W** Low energy consumption of 1W

### WARRANTY

Warranty	4 years
Battery Warranty	2 years

### FEATURES & BENEFITS

Interchangeable lens supplied making it easy to use the same product in both open area and corridor applications

High performance providing up to 17 metre spacings

Lithium iron phosphate LiFePO4 battery

Flexible battery compartment makes it easy to insert into a ceiling cut-out

