



Open area version



Corridor version



High efficacy of 140lm/W



Quick and easy installation with loop-in/loop-out connector



Low energy consumption of 2W

Salvus Surface

High Performance Emergency Spot

Features

IP rating	IP65
IK rating	IK04
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	0°C - 45°C
Weight	380g
Inrush Current	3A
Construction Material	Polycarbonate
Electric Class (1, 2, 3)	2
Battery	LiFePO4 3.2V 1500mAh
Install Connector Type	Integrated terminals, loop-in/loop-out
Mounting Options	Surface

Guarantee

Warranty	4 years
Battery Warranty	2 years

Features & benefits

- Interchangeable lens supplied making it easy to use the same product in both open area and corridor applications
- Lithium iron phosphate LiFePO4 battery

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm/W	EM lm
EMSWSQEM	White RAL9003	Manual-test	2W	6500K	165° / 160°x50°	140	280 Open - 230 Corridor
EMSWRDEM	White RAL9003	Manual-test	2W	6500K	165° / 160°x50°	140	280 Open - 230 Corridor
EMSBSQEM	Black RAL9005	Manual-test	2W	6500K	165° / 160°x50°	140	280 Open - 230 Corridor
EMSBRDEM	Black RAL9005	Manual-test	2W	6500K	165° / 160°x50°	140	280 Open - 230 Corridor

Wiring Information

Cable / Flying Lead	0.75-4.0mm ²
Type of Wiring Required	Parallel

Accessories

Office	Remote emergency lighting for mains lighting range	Sold Separately
Education	Remote emergency lighting for mains lighting range	Sold Separately
Retail	Remote emergency lighting for mains lighting range	Sold Separately
Hotel & Leisure	Remote emergency lighting for mains lighting range	Sold Separately

