



# SALVUS SURFACE

High Performance Emergency Spot

## FEATURES

IP rating	IP65
IK rating	IK04
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80

## INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C - 45°C
Weight	380g
Inrush Current	3A
Construction Material	Polycarbonate
Electric Class (1, 2, 3)	2
Battery	LiFePO4 3.2V 1500mAh
Install Connector Type	Integrated terminals, loop-in/loop-out
Mounting Options	Surface

## PHOTOMETRICS @ 25°C

Product code	Finish	Type	Colour	Beam	EM lm
EMWSQEM	White RAL9003	Manual-test	6500K	165° / 160°x50°	280 Open - 230 Corridor
EMSWRDEM	White RAL9003	Manual-test	6500K	165° / 160°x50°	280 Open - 230 Corridor
EMBSQEM	Black RAL9005	Manual-test	6500K	165° / 160°x50°	280 Open - 230 Corridor
EMBRDEM	Black RAL9005	Manual-test	6500K	165° / 160°x50°	280 Open - 230 Corridor

## WIRING INFORMATION

Cable / Flying Lead	0.75-4.0mm <sup>2</sup>
Type of Wiring Required	Parallel

## ACCESSORIES

Office	Remote emergency lighting for mains lighting range	Sold Separately
Education	Remote emergency lighting for mains lighting range	Sold Separately
Retail	Remote emergency lighting for mains lighting range	Sold Separately
Hotel & Leisure	Remote emergency lighting for mains lighting range	Sold Separately

- 140lm/W** High efficacy of 140lm/W
- Quick and easy installation** with loop-in/loop-out connector
- 2W** Low energy consumption of 2W

## WARRANTY

Warranty	4 years
Battery Warranty	2 years

## FEATURES & BENEFITS

Interchangeable lens supplied making it easy to use the same product in both open area and corridor applications

Lithium iron phosphate LiFePO4 battery

