



## SALVUS SURFACE

High Performance Emergency Spot

### FEATURES

<b>IP rating</b>	IP65
<b>IK rating</b>	IK04
<b>CSP Switchable</b>	Single CCT
<b>LED Lifetime</b>	L70 50,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Maintained / Non-Maintained</b>	Maintained, Non-Maintained

### INSTALLATION INFORMATION

<b>Input</b>	220-240V AC
<b>Maximum Ambient Temperature</b>	0°C - 45°C
<b>Weight</b>	380g
<b>Inrush Current</b>	3A
<b>Construction Material</b>	Polycarbonate
<b>Electric Class (1, 2, 3)</b>	II
<b>Battery</b>	LiFePO4 3.2V 1500mAh
<b>Install Connector Type</b>	Integrated terminals, loop-in/loop-out
<b>Mounting Options</b>	Surface

### PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	EM lm
<b>EMWSQEM</b>	White RAL9003	Manual-test	2W	6500K	165° / 160°x50°	280 Open - 230 Corridor
<b>EMSWRDEM</b>	White RAL9003	Manual-test	2W	6500K	165° / 160°x50°	280 Open - 230 Corridor
<b>EMBSQEM</b>	Black RAL9005	Manual-test	2W	6500K	165° / 160°x50°	280 Open - 230 Corridor
<b>EMBRDEM</b>	Black RAL9005	Manual-test	2W	6500K	165° / 160°x50°	280 Open - 230 Corridor

### WIRING INFORMATION

<b>Cable / Flying Lead</b>	0.75-4.0mm <sup>2</sup>
<b>Type of Wiring Required</b>	Parallel

### ACCESSORIES

<b>Office</b>	Remote emergency lighting for mains lighting range	Sold Separately
<b>Education</b>	Remote emergency lighting for mains lighting range	Sold Separately
<b>Retail</b>	Remote emergency lighting for mains lighting range	Sold Separately
<b>Hotel &amp; Leisure</b>	Remote emergency lighting for mains lighting range	Sold Separately

140lm/W

High efficacy of 140lm/W



Quick and easy installation with loop-in/loop-out connector

2W

Low energy consumption of 2W

### WARRANTY

Warranty	4 years
Battery Warranty	2 years

### FEATURES & BENEFITS

Interchangeable lens supplied making it easy to use the same product in both open area and corridor applications

Lithium iron phosphate LiFePO4 battery

