



LiFePO4 battery



Battery Temperature
Monitored



DALI-2 Addressable, Manual
& Self Test Option

WARRANTY

Warranty	5 years
Battery Warranty	5 years

FEATURES & BENEFITS

IP65 suitable for outdoor environments

Housing is rugged and made of polycarbonate

A rugged robust polycarbonate lens and housing

Self-test function can be easily disabled by removing green 2-pin jumper connector

SALVUS TWIN SPOT

520lm Emergency Twin Spot

FEATURES

IP rating	IP65
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 50,000h
Emergency Option	Yes, Self and DALI-2 Test

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C-40°C
Weight	1160g
Inrush Current	4A 62.5ms
Construction Material	PC Housing
Electric Class (1, 2, 3)	2
Battery	LiFePO4 3.2V 5500mAH
Install Connector Type	Push-fit terminal connector
Mounting Options	Surface

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	EM lm
EMTW5MS	White	2.8W	6500K	70°	520	520

WIRING INFORMATION

Type of Wiring Required	Parallel
-------------------------	----------

