



CSP CCT switchable 2700K, 3000K and 4000K



360° Even light distribution



IP65 ideal for car parks and walk ways

## Slim CSP Bollard

CCT Switchable IP65 Bollard

### Features

|                        |                |
|------------------------|----------------|
| IP rating              | IP65           |
| IK rating              | IK08           |
| CSP Switchable         | Switchable CCT |
| Dimmable Option        | Yes (TRIAC)    |
| LED Lifetime           | L80 100,000h   |
| Colour Rendering Index | CRI>80         |
| Colour Consistency     | SDCM6          |

### Installation Information

|                             |              |
|-----------------------------|--------------|
| Input                       | 220-240V AC  |
| Maximum Ambient Temperature | -15°C - 30°C |
| Weight                      | 625g         |
| Inrush Current              | 10A 0.4ms    |
| Construction Material       | Aluminum     |
| Electric Class (1, 2, 3)    | 1            |
| Earth Leakage               | 0.032mA      |
| Suitable for coastal areas  | No           |
| Mounting Options            | Surface      |
| Power Factor                | 0.95         |

### Guarantee

Warranty 5 years

### Features & benefits

- Choice of colours Black, Grey and Corten
- Available in 300mm and 600mm sizes
- Cable entry through base and expansion bolt installation kit included
- IP68 inline connector included

### Photometrics @ 25°C

| Product Code | Finish     | Beam | W   | Colour | lm  | lm/W | Energy |
|--------------|------------|------|-----|--------|-----|------|--------|
| BLSAG3RDSCS  | Anthracite | 120° | 14W | 2700K  | 720 | 56   |        |
|              |            |      |     | 3000K  | 770 | 62   |        |
|              |            |      |     | 4000K  | 800 | 58   |        |
| BLSBK3RDSCS  | Black      | 120° | 14W | 2700K  | 630 | 50   |        |
|              |            |      |     | 3000K  | 660 | 53   |        |
|              |            |      |     | 4000K  | 680 | 50   |        |
| BLSCN3RDSCS  | Corten     | 120° | 14W | 2700K  | 760 | 57   |        |
|              |            |      |     | 3000K  | 735 | 60   |        |
|              |            |      |     | 4000K  | 675 | 55   |        |
| BLSAG6RDSCS  | Anthracite | 120° | 14W | 2700K  | 720 | 56   |        |
|              |            |      |     | 3000K  | 770 | 62   |        |
|              |            |      |     | 4000K  | 800 | 58   |        |
| BLSBK6RDSCS  | Black      | 120° | 14W | 2700K  | 630 | 50   |        |
|              |            |      |     | 3000K  | 660 | 53   |        |
|              |            |      |     | 4000K  | 680 | 50   |        |
| BLSCN6RDSCS  | Corten     | 120° | 14W | 2700K  | 760 | 57   |        |
|              |            |      |     | 3000K  | 735 | 60   |        |
|              |            |      |     | 4000K  | 675 | 55   |        |

### Wiring Information

|                              |                              |
|------------------------------|------------------------------|
| Cable / Flying Lead          | H05RN-F 3G 1.0mm2            |
| Cable Required for Connector | 3x 0.75 - 2.5mm <sup>2</sup> |
| Type of Wiring Required      | Parallel                     |

### Accessories

|        |                             |                 |
|--------|-----------------------------|-----------------|
| SBEBX4 | Route mount Kit, J-Bolts X4 | Sold Separately |
|--------|-----------------------------|-----------------|

