



Switchable between 2200K and 3000K



360° even light distribution



IP66 ideal for outdoor areas

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

Installation spike included with product

Water ingress protection device included in cable

Can be dimmable based on driver used

A full range of aesthetic and installation accessories available

DC in Product Code = Domed Cover

FC in Product Code = Flat Cover

Product is delivered with Cover and Installation Spike as standard

Our anodised finish offers high corrosion resistance and excellent coastal protection, proven by a 1000hr salt mist test



SPYDRA CSP

CCT colour switchable LED low voltage spike light

FEATURES


IP rating	IP66
CSP Switchable	Switchable CCT
Tilttable (°)	Fixed
Dimmable Option	Driver dependent
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

INSTALLATION INFORMATION

Input	8-11V DC
Maximum Ambient Temperature	-20°C - 40°C
Weight	300mm: 631g, 600mm: 710g
Inrush Current	N/A
Construction Material	Aluminium
UK Bathroom Zone	N/A
SELV	N/A
Electric Class (1, 2, 3)	III
Earth Leakage	N/A
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	Energy
SPYB3DCS	Black	Domed Black	120°	3W	2200K	240	60	A t G E
				6.5W	3000K	310	77	
					2200K	450	56	
SPYA3DCS	Anthracite	Domed Grey	120°	3W	2200K	240	60	A t G E
				6.5W	3000K	310	77	
					2200K	450	56	
SPYB6DCS	Black	Domed Black	120°	3W	2200K	240	60	A t G E
				6.5W	3000K	310	77	
					2200K	450	56	
SPYA6DCS	Anthracite	Domed Grey	120°	3W	2200K	240	60	A t G E
				6.5W	3000K	310	77	
					2200K	450	56	
SPYB3FCS	Black	Flat Black	120°	3W	2200K	240	60	A t G E
				6.5W	3000K	310	77	
					2200K	450	56	
SPYA3FCS	Anthracite	Flat Grey	120°	3W	2200K	240	60	A t G E
				6.5W	3000K	310	77	
					2200K	450	56	
SPYB6FCS	Black	Flat Black	120°	3W	2200K	240	60	A t G E
				6.5W	3000K	310	77	
					2200K	450	56	
				3W	2200K	240	60	
				6.5W	3000K	310	77	
					2200K	450	56	
				3W	2200K	240	60	
				6.5W	3000K	310	77	
					2200K	450	56	
				3W	2200K	240	60	
				6.5W	3000K	310	77	
					2200K	450	56	



SPYA6FCS	Anthracite	Flat Grey	120°	3W	2200K	240	60
					3000K	310	77
					2200K	450	56
					3000K	580	73

WIRING INFORMATION

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	2 Core
Output Cable Type	3m H05RN-F rubberised cable (outside diameter: 6mm)

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV150700 (all settings)	220-240V	Yes	No	N/A		
DRV350700TD (700mA)	220-240V	Yes	Yes	N/A		
PSIP70018W	220-240V	Yes	No	1	1	2

ACCESSORIES

SPYBASEA	Spydra Base Plate for surface mounting, Grey	Sold Separately
SPYBASEB	Spydra Base Plate for surface mounting, Black	Sold Separately
SPYDCOVA	Spydra Domed Cover Round, Grey	Sold Separately
SPYDCOV B	Spydra Domed Cover Round, Black	Sold Separately
SPYFCOVA	Spydra Flat Cover, Grey	Sold Separately
SPYFCOV B	Spydra Flat Cover, Black	Sold Separately
SPYSPIKE	Spydra Spike Kit Accessory	Sold Separately

Spydra Spike Light adds charm and functionality to your outdoor space with its sleek design and durable build. It comes with an installation spike and water protection for a hassle-free setup. Dim it (with a compatible driver) to create the ideal ambiance, and select from domed or flat covers (both included). This low-voltage light provides excellent light output and even 360° distribution, all while remaining safe and effective. With an IP66 rating, it can withstand the elements and is ideal for gardens, pathways, and other applications. You can further personalise it with a variety of optional accessories (sold separately).