



C
collingwood



Switchable between 2200K and 3000K



360° even light distribution



IP66 ideal for outdoor areas

Features

IP rating	IP66
CSP Switchable	Switchable CCT
Tiltable	No
Dimmable Option	Driver dependent
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation Information

Input	8-11V DC
Maximum Ambient Temperature	-20°C - 40°C
Weight	300mm: 430g, 600mm: 510g
Inrush Current	N/A
Construction Material	Aluminium
UK Bathroom Zone	N/A
SELV	N/A
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Guarantee

Warranty 5 years

Features & benefits


- Installation spike included with product
- Water ingress protection device included in cable
- Can be dimmable based on driver used
- A full range of aesthetical and installation accessories available
- DC in Product Code = Domed Cover
- FC in Product Code = Flat Cover
- Product is delivered with Cover and Installation Spike as standard
- Grey RAL 7016, Black RAL 9005

Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	Energy
SPYB3DCS	Black	Domed Black	120°	3W	2200K	240	60	
					3000K	310	77	
				6.5W	2200K	450	56	
					3000K	580	73	
SPYA3DCS	Grey	Domed Grey	120°	3W	2200K	240	60	
					3000K	310	77	
				6.5W	2200K	450	56	
					3000K	580	73	
SPYB6DCS	Black	Domed Black	120°	3W	2200K	240	60	
					3000K	310	77	
				6.5W	2200K	450	56	
					3000K	580	73	
SPYA6DCS	Grey	Domed Grey	120°	3W	2200K	240	60	
					3000K	310	77	
				6.5W	2200K	450	56	
					3000K	580	73	
SPYB3FCS	Black	Flat Black	120°	3W	2200K	240	60	
					3000K	310	77	
				6.5W	2200K	450	56	
					3000K	580	73	
SPYA3FCS	Grey	Flat Grey	120°	3W	2200K	240	60	
					3000K	310	77	
				6.5W	2200K	450	56	
					3000K	580	73	
SPYB6FCS	Black	Flat Black	120°	3W	2200K	240	60	
					3000K	310	77	
				6.5W	2200K	450	56	
					3000K	580	73	
SPYA6FCS	Grey	Flat Grey	120°	3W	2200K	240	60	
					3000K	310	77	
				6.5W	2200K	450	56	
					3000K	580	73	

Wiring Information

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series





collingwood

Input Cable Type	2 Core
Output Cable Type	3m H05RN-F rubberised cable (outside diameter: 6mm)

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV150700 (all settings)	220-240V	Yes	No	N/A		
DRV350700TD (700mA)	220-240V	Yes	Yes	N/A		
PSIP70018W	220-240V	Yes	No	1	1	2

Accessories

SPYBASEA	Spydra Base Plate for surface mounting, Grey	Sold Separately
SPYBASEB	Spydra Base Plate for surface mounting, Black	Sold Separately
SPYDCOVA	Spydra Domed Cover Round, Grey	Sold Separately
SPYDCOVB	Spydra Domed Cover Round, Black	Sold Separately
SPYFCOVA	Spydra Flat Cover, Grey	Sold Separately
SPYFCOVB	Spydra Flat Cover, Black	Sold Separately
SPYSPIKE	Spydra Spike Kit Accessory	Sold Separately

Spydra Spike Light adds charm and functionality to your outdoor space with its sleek design and durable build. It comes with an installation spike and water protection for a hassle-free setup. Dim it (with a compatible driver) to create the ideal ambiance, and select from domed or flat covers (both included). This low-voltage light provides excellent light output and even 360° distribution, all while remaining safe and effective. With an IP66 rating, it can withstand the elements and is ideal for gardens, pathways, and other applications. You can further personalise it with a variety of optional accessories (sold separately).