



STRIP LED 230V

FEATURES

IP rating	IP65
IK rating	Other
CSP Switchable	Single CCT
Dimmable Option	Yes (Mains)
LED Lifetime	L70 B50 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Self-Adhesive Backing	True
Bespoke Lengths	Yes
Strip type	Flexible tape

INSTALLATION INFORMATION

Input	220-240V AC
Weight	0.38
Construction Material	Flexible Tape with Silicone Coating
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	II
Maximum Running Length	5 m

PHOTOMETRICS @ 25°C

Product code	W	Colour	Beam	lm	lm/W	Energy
70220/C/05	11W/m	3000K	120	1073	98	A+ G F
70220/C/20	11W/m	3000K	120	1073	98	A+ G F
70220/C/50	11W/m	3000K	120	1073	98	A+ G F
70220/N/05	11W/m	4000K	120	1157	105	A+ G E
70220/N/20	11W/m	4000K	120	1157	105	A+ G E
70220/N/50	11W/m	4000K	120	1157	105	A+ G E
70230/C/05	18W/m	3000K	120	1552	86	A+ G F
70230/C/20	18W/m	3000K	120	1552	86	A+ G F
70230/C/50	18W/m	3000K	120	1552	86	A+ G F
70230/N/05	18W/m	4000K	120	1690	94	A+ G E

WIRING INFORMATION

Cable / Flying Lead	N/A
Type of Wiring Required	Parallel



Ideal for accent lighting (11W) and primary lighting (18W)



Ideal for wet environments with IP65 rating



Quick and easy installation with self-adhesive backing

WARRANTY

Warranty

3 years

FEATURES & BENEFITS

230V long run solution for up to 50m from a single power supply

140 LEDs/m

Ideal for Hospitality Spaces, Hotel Receptions & Corridors, Building Façades, Large Gardens & Maintenance Areas

Cut intervals every 100mm

12mm width

Ideal for application in outdoor spaces and industrial environments

